

Genuine Restek Replacement Parts

PerkinElmer GCs



More Parts & Accessories
for More GC Systems

Agilent • Bruker/Varian • PerkinElmer • Shimadzu • Thermo Scientific • And More!

RESTEK

Innovative Chromatography Products

www.restek.com

More Parts & Accessories for More GC Systems

Agilent • Bruker/Varian • PerkinElmer • Shimadzu • Thermo Scientific • And More!

Dear Colleague,

Restek's GC Accessories Team is devoted to bringing you the highest-quality products, delivered on time every time, to help you maximize data reproducibility and minimize instrument downtime—regardless of which brand of instrument you use. From our exceptionally inert Sky® inlet liners on the right to the invaluable Restek Electronic Leak Detector on page 12, Genuine Restek Replacement Parts are designed to meet or even exceed GC manufacturers' already-strict specifications and performance requirements. And of course, as with all Restek products, we also offer exemplary Plus 1 service before and after you order.

Do you have a product suggestion or question about Restek's GC accessories? Feel free to contact one of our team members or your Restek representative today. We look forward to hearing from you!

Sincerely,

Scott Adams

GC Accessories Product Marketing Manager



Scott Grossman
GC Accessories
Chemist

Rob Lindquist
GC Accessories Associate
Product Marketing Manager

Kelli Steindl
GC Product
Line Manager

Scott Adams
GC Accessories Product
Marketing Manager

e-mail us at gcaccpmm@restek.com

Table of Contents

Sky® Inlet Liners.....	1–5
Other Deactivations.....	6
Other Inlet Liners.....	7–8
Inlet Liner Packing Materials.....	9
Inlet Liner Accessories.....	10
O-Rings, Septa, Adaptors.....	11
Leak Detector.....	12
Flowmeter.....	13
Tools.....	14–15
FID Supplies.....	15
Ferrules.....	16–17
Connectors.....	18–21
Vial Accessories.....	22
Vials.....	23–27
Syringes.....	28
Super-Clean Gas Filters.....	29
Gas Regulators & Accessories.....	30–31
Fittings.....	32–33
Fitting Kits.....	33



How can we help you today? Contact us...

customer **service**: 1-814-353-1300 (ext. 3) | e-mail: csreps@restek.com

technical **service**: 1-814-353-1300 (ext. 4) | e-mail: support@restek.com

sales representatives: 1-814-353-1300 | e-mail: salesreps@restek.com

3 ways to **order**:

1. **CALL**: 1-800-356-1688 (ext. 3) or 1-814-353-1300 (ext. 3)
Monday–Friday 8:00 a.m.–6:00 p.m. Eastern Time

2. **FAX**: 1-814-353-1309 24 hours a day

3. **ONLINE**: www.restek.com 24 hours a day

Outside the U.S.? Find a distributor at www.restek.com/distributor



Patent pending

True Blue Performance

- Increase accuracy and reproducibility with state-of-the-art deactivation.
- Achieve lower detection limits for a wide range of active compounds.
- Use wool with confidence—quartz wool is deactivated after packing, preventing the loss of sensitive analytes.

When faced with complex choices, simple solutions stand out. Sky® inlet liners from Restek use a comprehensive, state-of-the-art deactivation and are the only blue liners on the market—making them an easy-to-recognize solution to common inlet problems.

Sky® liners give you the inertness you need for more accurate trace-level results.

The innovative deactivation used for Sky® liners results in exceptional inertness for a wide range of analyte chemistries. By reducing active sites and enhancing analyte transfer to the column, these liners increase accuracy and precision, allowing lower detection limits for many active compounds. In addition to improved data quality, you'll benefit from fewer liner changes and less downtime for maintenance.

Selecting the right liner for your application can be a challenging task. Sky® inlet liners make the choice simple; the comprehensive deactivation, distinctive color, and availability in popular configurations mean Sky® liners are the best choice for optimizing chromatographic performance. Regardless of your application, Sky® liners provide reliable inertness and assured performance, day-after-day and analysis-after-analysis.



The Story Behind Sky® Liners

For over 25 years, Restek's vision has been to be the company chromatographers trust. This philosophy is the cornerstone of our business, and it's the reason our chemists and engineers are dedicated to developing innovative, best-in-class products like Sky® liners. As chromatographers, we understand your needs and strive to develop and deliver products that make your life easier.

With Sky® liners, our goal was to create a state-of-the-art deactivation that provides superior performance. But why did we make them blue? Restek has always been associated with the color blue; to us, it signifies strength, innovation, and excellence. We made Sky® liners blue because it represents the technological advancements and unmatched quality that define Restek products. Choose blue—the best choice for dependable results.

Simple Solutions:

Inert Sky® Inlet Liners Improve Accuracy and Precision for a Wide Range of Analytes



Many chromatographic problems, such as poor response and missing or tailing peaks, are caused by activity in the inlet liner. These effects complicate quantification and can be particularly problematic for sensitive analytes. Sky® inlet liners from Restek offer exceptional inertness, ensuring enhanced transfer of analytes to the column, good response, and highly symmetric peaks. The inertness of these liners is due to a state-of-the-art deactivation process that completely passivates the liner and wool so that they are inert to a wide variety of active analytes.

Some deactivations, such as base deactivation, are effective only for particular target compound chemistries. In contrast, the balanced deactivation of Sky® liners prevents interactions with many chemical classes. As shown on the following pages, complex pesticide probes, as well as both acidic and basic compounds have strong responses and excellent peak shapes, demonstrating the inertness of Sky® liners. With Sky® inlet liners, you will see improved sensitivity, accuracy, and reproducibility liner-to-liner, which allows you to quantify challenging compounds at trace levels with confidence.

Reduced Breakdown Improves Trace Analyses

Endrin and DDT are important analytes for the environmental and food safety industries, and they also serve as excellent general probes for liner inertness. Both compounds are sensitive to different modes of activity due to their chemical structures and their being analyzed at very low concentrations. As shown in Figure 1, Sky® liners are significantly more inert than comparable competitor liners, showing 3–4 times less endrin and DDT breakdown.

Figure 1: Endrin and DDT breakdown is significantly reduced with Sky® liners, demonstrating higher inertness.



Inert Sky® liners reduce analyte breakdown, giving you more accurate results.

	% Breakdown	
	Endrin	DDT
Restek	4.8	1.3
Competitor A	12	5.2

Peaks

1. DDE*
 2. Endrin
 3. DDD*
 4. Endrin aldehyde*
 5. DDT
 6. Endrin ketone*
- *breakdown products

GC_EV1200_1202

Column: Rxi®-5Sil MS, 15 m, 0.25 mm ID, 0.25 µm (cat.# 13620); **Sample:** Endrin (50 ng/mL) and DDT (100 ng/mL) in hexane; **Injection:** Inj. Vol.: 1 µL splitless (hold 0.75 min); **Liner:** Comparison of Sky® Single Taper Liner with Wool (cat.# 23303.5) and Agilent Single Taper Liner with Wool (cat.# 5062-3587); **Inj. Temp.:** 250 °C.; **Detector:** µ-ECD @ 300 °C.


did you know?

Sky® inlet liners from Restek are extensively tested to ensure consistent product quality. The color and label have been shown not to interfere with analyses or contribute to background. Choose blue—the best liner for sensitive applications.

Greater Inertness Results in Higher Analyte Response

Another common probe used to illustrate inertness is 2,4-dinitrophenol (2,4-DNP), which functions as an indicator of acid compound interactions. It is used to monitor system suitability in semivolatiles methods, which benefit from the use of wool to assist in sample vaporization. As shown in Figure 2, the response of 2,4-DNP with the Sky® inlet liner, even at low concentrations, is superior to a competitor's liner. The competitor liner with wool has active sites that adsorb 2,4-DNP and reduce its response. In contrast, an excellent response is achieved using the Sky® liner, even in the presence of wool.

Figure 2: The state-of-the-art deactivation used for Sky® liners with wool results in higher responses for active acid compounds, such as 2,4-DNP.



Increase the response of active analytes with inert Sky® inlet liners!

	2,4-DNP Response Factor
Restek	0.28
Competitor A	0.02

Peaks


1. Acenaphthene (IS)
2. 2,4-DNP

Column: Rxi®-5Sil MS, 15 m, 0.25 mm ID, 0.25 µm (cat.# 13620);
Sample: 10 µg/mL each 2,4-dinitrophenol and acenaphthene standard in methylene chloride; **Injection:** Inj. Vol.: 1 µL splitless (hold 1 min); **Liner:** Comparison of Sky® Single Taper Inlet Liner with Wool (cat.# 23303.5) and Agilent Single Taper Inlet Liner with Wool (cat.# 5062-3587); **Inj. Temp.:** 250 °C; **Detector:** FID @ 300 °C.

Comprehensive Deactivation Ensures Excellent Peak Shape

In addition to providing excellent results for active pesticides and acidic compounds, Sky® inlet liners are also highly inert to active basic compounds, such as underivatized amphetamines. The exceptional inertness of Sky® liners produces much better peak shape than is typically seen on other liners, resulting in simpler quantification and more accurate results (Figure 3).

Figure 3: Sky® liners are completely passivated. Even when using wool, peak shape for highly active underivatized amphetamine is excellent.



Peaks

1. Amphetamine


Column: Rxi®-5Sil MS, 30 m, 0.25 mm ID, 0.25 µm (cat.# 13623);
Sample: Amphetamine; Diluent: 1-chlorobutane; Conc.: ~10 µg/mL;
Injection: Inj. Vol.: 1 µL splitless (hold 1 min); **Liner:** Comparison of Sky® Single Taper with Wool (cat.# 23303.5) and SGE Single Taper with Wool (cat.# 092019); **Inj. Temp.:** 250 °C; **Purge Flow:** 20 mL/min; **Oven Temp:** 45 °C to 250 °C at 20 °C/min; **Carrier Gas:** He, constant flow; **Flow Rate:** 2 mL/min; **Detector:** FID @ 350 °C.; **Make-up Gas Flow Rate:** 45 mL/min; **Make-up Gas Type:** N₂; **Instrument:** Agilent 7890A GC

Liner-to-Liner Reproducibility: A Measure of Consistent Quality

It's not good enough to have one quality liner. You have to be confident that every liner will give the same level of performance. We test Sky® liners extensively to ensure that each one is exceptionally inert and will provide optimal results. Using endrin breakdown as a measure of reproducibility, the data in Figure 4, based on multiple lots, illustrate that Sky® liners are more consistently inert than competitor products.


Sky® liners provide exceptional inertness across a wide range of active analytes. The consistent, comprehensive deactivation process results in the accuracy and precision you need for reliable trace-level analyses. Simplify liner selection with Sky® liners from Restek—**choose blue, the best choice for dependable results.**

Figure 4: Sky® inlet liners from Restek consistently show less endrin breakdown than comparable liners from other sources.



Sky® inlet liners are easily recognizable for your reordering convenience. All Sky® liners come in specially marked boxes and are packaged in ultra-clean blister packs.

Sky® Inlet Liners for PerkinElmer GCs

Split Liners for PerkinElmer GCs	ID	Similar to PE part #	cat.#		
	OD x Length		ea.	5-pk.	
	4.0 mm	N6502009	23449.1	23449.5	
Splitter w/Wool	6.2 mm x 92.1 mm				
	4.0 mm	N6121020	23450.1	23450.5	
Split Precision Liner w/Wool	6.2 mm x 92.1 mm				
Splitless Liners for PerkinElmer GCs	ID	Similar to PE part #	cat.#		
	OD x Length		ea.	5-pk.	
	2.0 mm	N6121021	23451.1	23451.5	
Splitless w/Wool	6.2 mm x 92.1 mm				
PSS Liners for PerkinElmer GCs	ID	Similar to PE part #	cat.#		25-pk.
	OD x Length		ea.	5-pk.	
	2.0 mm	N6121004	23317.1	23317.5	23317.25
Auto SYS XL PSS Split/Splitless w/Wool	4.0 mm x 86.2 mm				

DI Liners for PerkinElmer GCs	ID	Similar to PE part #	cat.#	
	OD x Length		ea.	5-pk.
	4.0 mm		23452.1	23452.5
Open-Top Uniliner w/Wool	6.2 mm x 92.1 mm	N6502016		
	4.0 mm		23453.1	23453.5
Drilled Uniliner (hole near top)	6.2 mm x 92.1 mm	N6121022		
	4.0 mm		23454.1	23454.5
Drilled Uniliner (hole near bottom)	6.2 mm x 92.1 mm	N6502013		
Patent pending				



Also Available for Agilent, Bruker/Varian,
Shimadzu, and Thermo Scientific GCs



www.restek.com/sky



Siltek®-Deactivated
Inlet Liners

Intermediate Polarity (IP)–Deactivation

- Phenylmethyl-deactivated surface for better recovery of polar and nonpolar compounds.
- Compatible with most common solvents.
- Our standard deactivation—every clear Restek liner is IP deactivated unless otherwise requested.

Siltek®-Deactivation

For Siltek®-deactivated inlet liners, add the corresponding suffix number to the liner catalog number.

- Maximizes the inertness of the sample pathway with proprietary deactivation.
- Minimizes breakdown.
- Low bleed.
- Thermally stable.
- “Clean and green”—manufactured without the use of harmful organic solvents.
- Ideal for chlorinated pesticides.

The patented Siltek® deactivation process for liners produces a highly inert glass surface that features high temperature stability, extreme durability, and low bleed. Try Siltek® liners, guard columns, and connectors for better recovery of sample analytes.

qty.	Siltek Liner		Siltek Liner w/Wool		Siltek Liner w/CarboFrit	
each	-214.1	addl. cost	-213.1	addl. cost	-216.1	addl. cost
5-pk.	-214.5	addl. cost	-213.5	addl. cost	-216.5	addl. cost
25-pk.	-214.25	addl. cost	-213.25	addl. cost	-216.25	addl. cost

Base-Deactivation

For base-deactivated inlet liners, add the corresponding suffix number to the liner catalog number.

qty.	Base-Deactivated Liner		Base-Deactivated Liner w/ Base-Deactivated Wool		Base-Deactivated Liner w/CarboFrit	
each	-210.1	addl. cost	-211.1	addl. cost	-229.1	addl. cost
5-pk.	-210.5	addl. cost	-211.5	addl. cost	-229.5	addl. cost
25-pk.	-210.25	addl. cost	-211.25	addl. cost	-229.25	addl. cost

Don't Forget Routine Maintenance

Inlet liners are the key to good injection port maintenance; changing them regularly helps prevent problems such as:

- Sample degradation resulting in poor response.
- Sample adsorption resulting in poor peak shape (tailing).
- Sample discrimination.
- Irreproducibility.
- Extraneous peaks from contamination or cored septum particles.

Finally, be sure to condition your liners at 20 °C higher than the operating inlet temperature for a minimum of 10 minutes to prepare them for use. By following these basic tips, you can avoid inlet problems and improve chromatographic performance.






Looking for the Best Solution?

Sky® inlet liners, featuring a state-of-the-art deactivation, give you the inertness you need for accurate, reproducible trace-level results.

See pages 1–5 for details.


Split Liners for PerkinElmer GCs	Benefits/Uses:	ID* OD x Length	Similar to PE part #	ea.	cat.# 5-pk.	25-pk.
 Straight	universal, for most common analyses	3.5 mm 5.0 mm x 100 mm	N6502008	20736	20737	—
 Auto SYS Splitter w/Deact. Wool	universal for most common analyses	4.0 mm 6.2 mm x 92.1 mm	N6502009	20832	20833	20834
 Auto SYS Cup Splitter	high & low MW compounds	4.0 mm 6.2 mm x 92.1 mm	N6502011	20835	20836	—
 Auto SYS Cyclosplitter	dirty samples, many injections before cleaning required	4.0 mm 6.2 mm x 92.1 mm	N6502012	20910	20911	—
 Auto SYS Laminar Cup Splitter	high MW compounds	4.0 mm 6.2 mm x 92.1 mm	—	20827	20828	—
 Auto SYS Split Precision Liner w/Deact. Wool	dirty samples, trace samples	4.0 mm 6.2 mm x 92.1 mm	N6121020	21026	21027	—

Splitless Liners for PerkinElmer GCs	Benefits/Uses:	ID* OD x Length	Similar to PE part #	ea.	cat.# 5-pk.	25-pk.
 Splitless (2 mm ID)	trace samples	2.0 mm 5.0 mm x 100 mm	N6502007	20730	20731	20732
 Auto SYS Splitless	headspace, purge & trap	1.0 mm 6.2 mm x 92.1 mm	N6502006	21272	21273	21274
 Auto SYS Splitless (2 mm ID) w/Deact. Wool	trace samples	2.0 mm 6.2 mm x 92.1 mm	N6121021	20829	20830	—
 Auto SYS Double Taper	trace, active samples up to 4 µL	4.0 mm 6.2 mm x 92.1 mm	N6502003	20853	20854	—
 Auto SYS Cyclo Double Taper	trace, dirty, active samples, up to 4 µL	4.0 mm 6.2 mm x 92.1 mm	N6502005	20899	20900	—


PSS Liners for PerkinElmer GCs	Benefits/Uses:	ID* OD x Length	Similar to PE part #	ea.	cat.# 5-pk.
 PSS Split/Splitless (1 mm ID)	trace samples	1.0 mm 4.0 mm x 86.2 mm	N6121006	20738	20741
 Auto SYS XL PSS Split/Splitless w/Deact. Wool	most common analyses	2.0 mm 4.0 mm x 86.2 mm	N6121004	21717	21718
 PSS Drilled Uniliner (hole near top)	trace, active samples, high recovery & linearity	2.0 mm 4.0 mm x 86.2 mm	—	22986	22987

*Nominal ID at syringe needle expulsion point.

All liners are shipped with intermediate polarity (IP) deactivation unless otherwise requested.
See page 6.

Zero Dilution Liners for PerkinElmer Auto SYS and Clarus GCs	Benefits/Uses:	ID* OD x Length	Similar to PE part #	ea.	cat.# 5-pk.
	headspace analysis	1.0 mm 2.0 mm x 73 mm	N1011446	22990	22991
Zero Dilution Inner Liner					
	headspace analysis	2.5 mm 6.2 mm x 90 mm	N1011445	22992	22993
Zero Dilution Outer Liner					

Zero Dilution Liners for PerkinElmer GCs with PSS Inlets	Benefits/Uses:	ID* OD x Length	Similar to PE part #	ea.	cat.# 5-pk.
	headspace analysis	1.0 mm 2.0 mm x 73 mm	N1011446	22990	22991
Zero Dilution Inner Liner					
	headspace analysis	2.5 mm 4.2 mm x 83 mm	N1011447	24978	24979
Zero Dilution Outer Liner					

DI Liners for PerkinElmer GCs (For 0.25/0.32/0.53 mm ID Columns)	Benefits/Uses	ID* OD x Length	Similar to PE part #	ea.	cat.# 5-pk.
	trace, dirty, active samples, high recovery & linearity	4.0 mm 6.2 mm x 92.1 mm	N6502016	20837	20838
Auto SYS Open-Top Uniliner w/Deact. Wool					
	trace, dirty, high MW active samples, high linearity	4.0 mm 6.2 mm x 92.1 mm	N6502017	20839	20840
Auto SYS Cyclo-Uniliner					
	trace, active samples, high recovery & linearity	4.0 mm 6.2 mm x 92.1 mm	N6121022	20819	20822
Auto SYS Drilled Uniliner (hole near top)					
	trace, active samples, high recovery & linearity	4.0 mm 6.2 mm x 92.1 mm	N6502013	21293	21294
Auto SYS Drilled Uniliner (hole near bottom)					
	trace, active samples, high recovery & linearity	4.0 mm 6.2 mm x 92.1 mm	N6502014	21295	21296
Auto SYS Single Taper Drilled Uniliner (hole near top)					

*Nominal ID at syringe needle expulsion point.

All liners are shipped with intermediate polarity (IP) deactivation unless otherwise requested. See page 6.



Restek can provide any of the liners shown deactivated by one of three processes, including highly inert Siltek® coating. Ordering information is on **page 6**.



Packing materials, including wool and CarboFrit® inserts, can be provided in any liner—subject to the liner ID and geometry. Ordering information is on **page 9**.



Siltek® Treated Liners



24324

Deactivated Wool

- More inert than our traditional fused silica wool.
- Use to vaporize a sample in a liner prior to introduction into a capillary column.

Description	qty.	cat.#
Deactivated Wool	10 grams	24324



20999

Base-Deactivated Wool

Ideal for amines and other basic compounds.

Description	qty.	cat.#
Base-Deactivated Wool	10 grams	20999

Packed Inlet Liners

Let Restek do the work! Just add the appropriate suffix to the liner catalog number.

qty.	Wool	CarboFrit	
ea.	-200.1	-209.1	addl. cost
5-pk.	-200.5	-209.5	addl. cost
25-pk.	-200.25	-209.25	addl. cost

†CarboFrit® inserts require a neck greater than 2 mm.

CarboFrit® Inlet Liner Packing Material

- Highly inert.
- Extends analytical column lifetime.
- Enhances reproducibility of split and splitless injections.
- Uniform pore size and consistent packing density guarantee consistent flow through the liner.
- Easy to install in any liner with an ID > 3.5 mm when using puller-insertor tool listed below.*




Add the corresponding suffix number to the liner catalog number.

qty.	suffix	
ea.	-209.1	addl. cost
5-pk.	-209.5	addl. cost
25-pk.	-209.25	addl. cost

*Liners with IDs less than 3.5 mm are difficult to pack. We will pack them on a custom basis (minimum neck ID of 2 mm required).

Replacement CarboFrit® Inserts

Description	qty.	cat.#
Frits for liner ID ≤ 4 mm	10-pk.	20295
Frits for liner ID > 4 mm	10-pk.	20294



21642

CarboFrit® Puller/Insertor Tool

- Hook end for removing CarboFrit® inserts.
- Bent end (90°) for inserting CarboFrit® inserts.


Description	qty.	cat.#
CarboFrit Puller/Insertor Tool	ea.	21642



tech
tip

Use of Packings With an Autosampler

We recommend using an injection port liner with wool or CarboFrit® packing when making injections with an autosampler. If there is no packing material in the liner, the solvent droplets act like water on a hot iron: they bounce around until vaporized (Leidenfrost phenomenon). Because autosamplers make rapid injections, samples can be incompletely vaporized, leading to nonreproducible peak response and tailing. You can prevent this by using wool or CarboFrit® packing material in the splitless liner to provide a surface for the solvent droplets to "sit" on until the heat from the injector vaporizes them.



Mini Wool Puller/Inserter

Insert and remove wool plugs easily. Order a spare pack so you'll always have one available.



Description	qty.	cat. #
Mini Wool Puller/Inserter	2-pk.	20114



Eliminates user variation!

Inlet Liner Packing Tool

- Position wool reproducibly every time.
- Accurate to a specific, measured depth.
- Can be used with all manufacturers' liners.



Loosen the nut on the side of the tool and adjust the gauge to the manufacturer's recommended depth.

Place a plug of loosely bound wool at the top of the inlet liner.

Insert the liner packing tool into the liner until the tool bottoms out. Remove the tool. The wool is now positioned correctly in the liner and the liner is ready for use.

Description	qty.	cat. #
Inlet Liner Packing Tool	ea.	20339

Recommended for inlet liners with an ID $\geq$ 2 mm.



No more burned fingers!

Inlet Liner Removal Tool

- Easily remove liner from injector—no more burned fingers.
- Made from high-temperature silicone.
- Won't chip or crack the liner.



Description	qty.	cat. #
Inlet Liner Removal Tool	3-pk.	20181



The Claw and The Claw Holder Kit

- Easily removes hot liners from injection ports.
- 4 mL vials (not included) can be replaced when dirty.

Never again will you burn your fingers removing a hot injection port liner. The Claw safely and cleanly removes liners, O-rings, or other small objects from the injection port. You can then place the hot objects in a clean 4 mL vial situated in The Claw holder until ready for reuse.



Description	qty.	cat. #
The Claw	ea.	26261
The Claw Holder Kit (includes The Claw and holder)	kit	26262
WISP 48 Snap Seal Vial	100-pk.	24658



Injector Maintenance

Approximately ninety percent of "bad" chromatography is traceable to problems in the injection port. These problems include contaminated carrier gas, incorrect injector flows, active or dirty sites on inlet seals and liners, improper use of wool, leaks, backflash, discrimination, incorrect injector temperature, poor column installation, and use of the wrong injection technique. To minimize injection port problems, set up a routine maintenance schedule and be sure to investigate the injector first when troubleshooting.

Graphite O-Rings for
PerkinElmer Auto SYS XL or
Clarus GCs With PSS Injector
Fits 4 mm OD liners



Description	Max. temp.	Similar to PE part #	qty.	cat.#
Graphite O-Rings for PerkinElmer Auto SYS XL or Clarus GCs w/PSS Injector	450 °C	N610-1751	10-pk.	21475
	450 °C	N610-1751	25-pk.	21476

Viton® O-Rings for
PerkinElmer PSS Injector
Fits 4 mm OD liners



Description	Max. temp.	Similar to PE part #	qty.	cat.#
Viton O-Rings for PerkinElmer PSS Injector	250 °C	N6101747	10-pk.	20366

Silicone O-Rings for PerkinElmer
Auto SYS XL or Clarus With CAP Injector
Fits 6.2 mm OD liners



Description	Max. temp.	Similar to PE part #	qty.	cat.#
Silicone O-Rings for PerkinElmer Auto SYS XL or Clarus w/CAP Injector	250 °C	N6101374	10-pk.	20262



Thermolite® Septa

Premium Non-Stick
BTO® Septa

Septa (11 mm) for PerkinElmer GCs

- Preconditioned and ready to use.
- Packaged in precleaned glass jars.

Thermolite Septa usable to 340 °C inlet temp.		Premium Non-Stick BTO Septa usable to 400 °C inlet temp.	
qty.	cat.#	qty.	cat.#
25-pk.	27141	50-pk.	27090
50-pk.	27142	100-pk.	27091
100-pk.	27143		

*Minimum recommended operating temperature for Premium Non-Stick BTO septa is 250 °C.

Merlin Microseal Septa

for PerkinElmer GCs

400 °C max injection port temperature.

The advantages of the Merlin Microseal Septum include elimination of septum coring, longer life, and consistently low needle-insertion force. The Microseal septum incorporates two separate sealing mechanisms. These sliding seals eliminate septum coring and the resulting accumulation of septum crumbs in the injection port liner.



22781

The Microseal septum uses a 23-gauge (0.63 mm, 0.025") needle or probe with a blunt, truncated conical tip. Since the syringe plunger end details are determined by manual or autosampler compatibility, often a removable needle syringe is an effective way to match both of these requirements. Installation is simple, requiring no modification of the injection port.

Description	Merlin#	Similar to PE#	cat.#
General Purpose Kit for PerkinElmer GCs (3 to 100 psi) Includes: Nut, Adapter, O-Ring & 2 General-Purpose (#410) Microseals	51-12	N9303344	22781
Replacement Microseals			
General-Purpose Microseal (most applications, 3 to 100 psi)	410	—	22812
Low-Pressure Microseal (1 to 45 psi)	310	—	22815
Microseal for SPME Applications (3 to 100 psi)	21-01	N9303345	22782



22318



22319



22320

Injector Adaptors for PerkinElmer Auto SYS XL

- Made of high-quality stainless steel.
- Meet or exceed original manufacturer's performance.
- Siltek®-treated version available for increased inertness.

Description	Similar to PE part #	qty.	cat.#
For use with PE-style capillary nuts			
Injector Adaptor for PerkinElmer Auto SYS XL	N6100157	ea.	22318
Siltek-Treated Injector Adaptor for PerkinElmer Auto SYS XL	—	ea.	22320
For use with 1/16" compression-style nuts			
Injector Adaptor for PerkinElmer Auto SYS XL	—	ea.	22319



22839

restek recommends

When your Leak Detector batteries need to be replaced, send the unit to us for a routine maintenance review to ensure continued sensitivity and reliability. We will replace not only the batteries, but also the probe and internal/external tubing. We will also recertify your unit. Contact Customer Service to send in your Leak Detector for maintenance (cat. #22839-R).



Carrying/storage case included with purchase of unit.



22658

Verify hard-to-reach leaks using the small probe adaptor (sold separately).

Restek Electronic Leak Detector

Don't let a small leak turn into a costly repair—protect your instrument and analytical column by using a Restek Leak Detector.

Features & benefits include:

- Optimized sample flow path.
- Ergonomic, handheld design.
- Rugged side grips for added durability.
- Handy probe storage for cleanliness and convenience.
- Long-lasting battery; up to 6 hours of continuous use.
- Automatic shutoff.
- A convenient carrying and storage case.
- Easy-to-clean probe assembly.
- A universal charger set (U.S., European, UK, and Australian plugs included).

Backed by a 1-year warranty, the Restek Leak Detector is the industry standard for performance and affordability in handheld leak detectors.

Leak Detector Facts

Detectable Gases:	Helium, nitrogen, argon, carbon dioxide, hydrogen
Battery:	Rechargeable Ni-MH internal battery pack (6 hours normal operation)
Operating Temperature Range:	32–120 °F (0–48 °C)
Humidity Range:	0–97%
Warranty:	One year
Certifications:	CE, Ex, Japan
Compliance:	WEEE, RoHS

Limits of Detection

These gases can be detected with the Restek Electronic Leak Detector at the following leak rates:

Minimum Detectable Gas Limits and Indicating LED Color:

- Helium, 1.0×10^{-5} , red LED
- Hydrogen*, 1.0×10^{-5} , red LED
- Nitrogen, 1.4×10^{-3} , yellow LED
- Argon, 1.0×10^{-4} , yellow LED
- Carbon Dioxide, 1.0×10^{-4} , yellow LED

Gas detection limits measured in atm cc/sec

Description	qty.	cat.#
Leak Detector With Hard-Sided Carrying Case and Universal Charger Set (U.S., UK, European, Australian)	ea.	22839
Leak Detector Routine Maintenance Review	ea.	22839-R
Soft-Side Storage Case	ea.	22657
Small Probe Adaptor	ea.	22658

Avoid using liquid leak detectors on a GC! Liquids can be drawn into the system.

*Caution: The Restek Electronic Leak Detector is designed to detect trace amounts of hydrogen in a noncombustible environment. It is NOT designed for determining leaks in a combustible environment. A combustible gas detector should be used for determining combustible gas leaks under any condition. When using it to detect hydrogen, the Restek Electronic Leak Detector may only be used for determining trace amounts in a GC environment.



Checking for leaks maintains the integrity of a GC system.

Restek ProFLOW 6000 Electronic Flowmeter

State-of-the-art features include:

- Measures volumetric flow for gases across a range of 0.5–500 mL/min.
- NIST traceable calibration.
- Ex rating (electrical apparatus for explosive gas atmospheres) for hydrogen and related gas types.
- Accuracy of $\pm 2\%$ of flow reading or ± 0.2 mL/min, whichever is greater.
- Over-range warning indicator.
- Auto shutoff feature.
- Use as a benchtop or handheld unit.
- Ergonomic design and side grips for comfort.
- Measures most gas types.*
- Convenient carrying/storage case included.
- Uses 2-AA batteries (included).
- Data output via USB port.
- 1-year warranty.
- Recalibration service available.

Flowmeters that can measure flammable gases are becoming mandatory, due to the increased use of hydrogen in chromatography. With its Ex rating, the Restek ProFLOW 6000 Flowmeter is designed specifically with explosive and flammable gases in mind.

The Restek ProFLOW 6000 is the only flowmeter you need for any type of chromatography gas measurement because of its wide range of capabilities. The ProFLOW 6000 is an electronic device capable of measuring volumetric flow for most gases. Real-time measurements can be made for various types of flow paths, including continually changing gas types. This portable unit is designed for easy handheld use, and the stand adds benchtop convenience.

Flowmeter Facts:

Type of Flowmeter:	Volumetric
Battery:	2-AA
Operating Temp. Range:	32–120 °F (0–48 °C)
Warranty:	One year
Certifications:	CE, Ex
Compliance:	WEEE, RoHS

Description

Description	qty.	cat.#
Restek ProFLOW 6000 Electronic Flowmeter With Hard-Sided Carrying Case	ea.	22656
ProFLOW 6000 Recalibration Service	ea.	22656-R
Soft-Side Storage Case	ea.	22657

*The flowmeter is designed to measure clean, dry, non-corrosive gases.



restek recommends

Recalibrate your ProFLOW 6000 Flowmeter once every year. Prolonged failure to recalibrate your unit may result in increased error. To always get the most accurate flow measurements, contact Customer Service to send in your flowmeter for recalibration (cat.# 22656-R).

Scoring Wafer With Handle

- Ceramic wafer is straight-edged for cutting fused silica tubing cleanly.
- Unique, ergonomic handle is made of soft, comfortable rubber.



23015



Hold tubing firmly in one hand, allowing about two inches to extend freely. Hold the scoring wafer at a 45° angle to the tubing. Exert just enough pressure to put a slight arc in the tubing. Pull perpendicularly across the tubing.



The tubing should fall off on its own, or it should easily break at the score with a slight tap of the wafer.



Check the cut against the white of the scoring wafer. Look for a clean, square cut.

Description	qty.	cat.#
Scoring Wafer With Handle	2-pk.	23015

Ceramic Scoring Wafer

- Four straight scoring edges for cutting fused silica tubing and four serrated edges for cutting MXT® metal capillary columns.



20116



Exert just enough pressure to put a slight arc in the tubing. Pull perpendicularly across the tubing. The tubing should fall off or break with a slight tap of the wafer.



Check the cut against the white of the scoring wafer. Look for a clean, square cut.

Description	qty.	cat.#
Ceramic Scoring Wafers	5-pk.	20116

Septum Puller

- Use hooked end for removing septa and O-rings; pointed end works well for removing stuck ferrules or debris.
- Keep several on hand in your laboratory—can be used in many different ways.



Remove a septum without damaging an expensive weldment.



Dislodge a stuck ferrule quickly and easily—without scoring the fitting.



20117

Description	qty.	cat.#
Septum Puller	ea.	20117



save money!

Save money on column installation tools by purchasing the MLE Capillary Tool Kit. See page 15.



27194

GC-MS Cleaning Kit

The Restek GC-MS Cleaning Kit (cat.#s 27194, 27195) includes:

- lint-free nylon gloves (small-2 pair)
- lint-free nylon gloves (large-2 pair)
- lint-free cotton cloth, 9 x 9 (10-pk.)
- micro mesh 4 x 6 sheet (4-pk.)
- aluminum oxide (1-kg jar)
- cotton tip applicators
- tweezers, large
- tweezers, small
- septum puller
- Dremel® tool, battery-operated (optional, 27194)
- tool kit bag

Reorder Kit (cat.# 27196) includes:

- lint-free nylon gloves (small-2 pair)
- lint-free nylon gloves (large-2 pair)
- lint-free cotton cloth, 9 x 9 (10-pk.)
- micro mesh 4 x 6 sheet (4-pk.)

Poor sensitivity, loss of sensitivity at high masses, or high multiplier gain during an auto tune are all indicators that your mass spectrometer source may need to be cleaned. Restek has assembled all of the necessary components for cleaning and polishing your ion source.

Description	qty.	cat.#
Mass Spec Cleaning Kit With Dremel Tool	kit	27194
Mass Spec Cleaning Kit Without Dremel Tool	kit	27195
Mass Spec Cleaning Kit Replacement Parts Kit	kit	27196
Includes: cloths, micro mesh sheets, small and large gloves		

26261



The Claw and The Claw Holder Kit

- Easily removes hot liners from injection ports.
- 4 mL vials (not included) can be replaced when dirty.

Never again will you burn your fingers removing a hot injection port liner. The Claw safely and cleanly removes liners, O-rings, or other small objects from the injection port. You can then place the hot objects in a clean 4 mL vial situated in The Claw holder until ready for reuse.



Description	qty.	cat. #
The Claw	ea.	26261
The Claw Holder Kit (includes The Claw and holder)	kit	26262
WISP 48 Snap Seal Vial	100-pk.	24658



MLE
Make Life
Easier!

22185

Everything you need
in one complete kit!

Make Life Easier (MLE) Capillary Tool Kit for PerkinElmer GCs

Includes:

- 1/8", 3/16", and 1/4" nylon brushes
- 1/4", 3/8", and 3/16" stainless steel wire tube brushes
- stainless steel surface brush
- 6 stainless steel jet reamers (0.25–0.65 mm OD)
- 1/4" x 5/16" open end wrench
- 3/8" x 1/16" open end wrench
- 7/16" x 1/2" open end wrench
- 1/2" x 9/16" open end wrench
- rubber-tipped slide-lock tweezers
- scoring wafers
- inlet liner removal tool
- septum puller
- mini wool puller/insertor tool
- 4-inch tapered needle file
- swivel head flashlight
- mini hand drill set
- 15 cm compact steel ruler
- pocket magnifier
- high-temperature string (1 meter)
- pipe cleaner (12-inch)
- cotton tip swabs (pk. of 25)

Description	qty.	cat. #
MLE Capillary Tool Kit	kit	22185



23038

FID Replacement Parts for PerkinElmer Auto SYS XL and Clarus 500

- Made of high-quality stainless steel.
- Meet or exceed original manufacturer's performance.

Description	Similar to PE part #	qty.	cat. #
FID Jet for PerkinElmer Auto SYS XL and Clarus 500	N6100361	ea.	23038
Auto-Ignite FID Replacement Part Kit for PerkinElmer Auto SYS XL and Clarus 500	N6103167, N6103175, N6101085, N6001204, 09912223	kit	23061
Nozzle Insulator for PerkinElmer Auto SYS XL and Clarus 500	N6101085	ea.	23062
FID Body for PerkinElmer Auto SYS XL and Clarus 500	N6100364	ea.	23063

FID Capillary Column Adaptors for PerkinElmer Auto SYS XL

- Made of high-quality stainless steel.
- Meet or exceed original manufacturer's performance.



Description	Similar to PE part #	qty.	cat. #
For use with PE-style capillary nuts			
FID Capillary Column Adaptor for PerkinElmer Auto SYS XL	N6120020	ea.	22608
For use with 1/16" compression-style nuts			
FID Capillary Column Adaptor for PerkinElmer Auto SYS XL	—	ea.	22609

also available

Restek now carries Swagelok® fittings in brass & stainless steel. See pages 32–33.





Choosing the Right Ferrule

Graphite ferrules are soft, easy to seal, stable to 450 °C, and contain no binders that might off-gas. Vespel®/graphite ferrules work better for vacuum and high-pressure applications (e.g., GC-MS) because they will not fragment or allow oxygen to permeate into the system, whereas graphite ferrules will. Because Vespel®/graphite ferrules are made from a harder material, they might require retightening after several temperature cycles. Alumaseal® ferrules are ideal for GC-MS. They will not crack or fragment and require no retightening after temperature cycles.

Vespel® Ferrules

- 100% high-temperature polyimide.
- Stable to 350 °C.
- Durable, leak-tight.



Vespel® ferrules

Graphite Ferrules

- Preconditioned to eliminate out-gassing.
- High-purity, high-density graphite.
- Smoother surface and cleaner edges than conventional graphite ferrules.
- Contain no binders that can off-gas or adsorb analytes.
- Stable to 450 °C.

Vespel®/Graphite Ferrules

- 60%/40% Vespel®/graphite blend offers the best combination of sealing and ease of workability.
- Seal with minimal torque, reusable, and preferred for vacuum and high-pressure uses.
- Stable to 400 °C.
- Recommended for mass spec transfer lines.

Capillary Ferrules for 1/16-Inch Compression-Type Fittings

Available in Vespel®, graphite, or Vespel®/graphite material.


Ferrule ID	Fits Column ID	qty.	Vespel	Graphite	Vespel/Graphite
0.3 mm		10-pk.	22213	20233	20275
0.4 mm	0.10/0.15/0.18/0.25/0.28 mm	10-pk.	22214	20200	20211
0.4 mm	0.10/0.15/0.18/0.25/0.28 mm	50-pk.	—	20227	20229
0.5 mm	0.32 mm	10-pk.	22215	20201	20212
0.5 mm	0.32 mm	50-pk.	—	20228	20231
0.6 mm	0.28 mm**	10-pk.	—	—	20232
0.8 mm	0.45/0.53 mm	10-pk.	22216	20202	20213
0.8 mm	0.45/0.53 mm	50-pk.	—	20224	20230
1.0 mm	0.75 mm*	10-pk.	22217	21058	24912
1.2 mm	0.75 mm*	10-pk.	22218	—	—
1.6 mm	1.00 mm*	10-pk.	—	21060	—

*For micropacked columns.

**For 0.28 mm MXT columns.



graphite ferrules



encapsulated graphite ferrules

Encapsulated Ferrules for 1/16-Inch Compression Fittings

- Reusable—will not deform and stick in fittings.
- Less torque needed to seal ferrule.
- Restek's unique blend of graphite minimizes fragmentation and out-gassing.

Ferrule ID	Fits Column ID	qty.	cat. #
0.4 mm	0.25 mm	10-pk.	21036
0.5 mm	0.32 mm	10-pk.	21037
0.8 mm	0.53 mm	10-pk.	21038

Standard Ferrules for 1/16-, 1/8-, and 1/4-Inch Fittings

Available in Vespel®, graphite, or Vespel®/graphite material.

Fitting Size	Ferrule ID	qty.	Vespel	Graphite	Vespel/Graphite
1/4"	3/16"	5-pk.	—	—	20258
1/16"	1/16"	10-pk.	22210	20207	20218
1/8"	1/8"	10-pk.	22211	20208	20219
1/8"	reduce to 1/16"	10-pk.	—	20209	20220
1/4"	1/4"	10-pk.	22212	20210	20221
1/4"	reduce to 1/8"	10-pk.	22219	20225	20222
1/4"	reduce to 1/16"	10-pk.	—	20226	20223



graphite ferrules

Two-Hole Ferrules for 1/8-Inch and 1/16-Inch Compression-Type Fittings

Fitting Size	Ferrule ID	Fits Column ID	qty.	Vespel/Graphite
1/16"	0.4 mm	0.25/0.28 mm	5-pk.	24848
1/16"	0.5 mm	0.32 mm	5-pk.	24849
1/8"	0.8 mm	0.45/0.53 mm	5-pk.	20246

Reducing Ferrules

Available in graphite or Vespel®/graphite material.

Fitting Size	Ferrule ID	Fits Column ID	qty.	Graphite	Vespel/Graphite
1/8"	0.4 mm	0.25 mm	5-pk.	20205	20254
1/8"	0.5 mm	0.32 mm	5-pk.	20205	20255
1/8"	0.8 mm	0.53 mm	5-pk.	20206	20215
1/4"	0.4 mm	0.25 mm	5-pk.	20203	—
1/4"	0.5 mm	0.32 mm	5-pk.	20203	20257
1/4"	0.8 mm	0.45/0.53 mm	5-pk.	20204	20217


Blank Ferrules for 1/16-Inch Fittings

Fitting Size	Ferrule ID	qty.	Vespel/Graphite
1/16"	no hole	10-pk.	20240

Alumaseal® Ferrules

- Aluminum construction—will not crack or fragment.
- No retightening required after temperature cycles—excellent for GC-MS.
- Eliminate out-gassing and make leak-tight seals for less detector noise.
- Unique two-piece design permanently locks on fused silica tubing without causing breakage.
- Will not stick in fittings, unlike Vespel® or graphite ferrules.
- Stable to 550 °C.
- Use with any 1/16" compression-type fitting.

Ferrule ID	Fits Column ID	qty.	cat.#
0.4 mm	0.25 mm	10-pk.	21472
0.5 mm	0.32 mm	10-pk.	21473
0.8 mm	0.53 mm	10-pk.	21474




- Will not crack or fragment.
- Excellent for GC-MS.

PTFE Ferrules

- Upper temperature limit 250 °C.
- 100% PTFE; completely inert.
- One-piece design requires no back ferrule.

Fitting Size	Ferrule ID	qty.	cat.#
1/16"	1/16"	10-pk.	21122
1/16"	0.4 mm	10-pk.	21123
1/16"	0.5 mm	10-pk.	21124
1/16"	0.8 mm	10-pk.	21125
1/8"	1/8"	10-pk.	21126
3/16"	3/16"	10-pk.	21127
1/4"	1/4"	10-pk.	21128






Fit both Restek cage designs.

**Secure, reliable
column-to-column
connections!**

NOTE: This product is not recommended for GC column-to-MS connections—use the Vacuum Vu-Union® union for this type of connection.



Vu2 Union® Connectors

- Connect a guard column to an analytical column.
- Connect a column to a transfer line.
- Connect two columns in series.
- Repair a broken column.
- Fit both Restek cage designs.

Restek's Vu2 Union® connector combines the simplicity of a Press-Tight® union with the strength of a metal union.



How does a Vu2 Union® connector work?

A Press-Tight® union in the Vu2 Union® connector joins the fused silica tubing ends together; the ferrule and knurled nut at each end of the connector hold the tubing in place via a secondary seal between the ferrule and the Press-Tight® union. Each knurled nut applies independent pressure to each ferrule to make leak-tight seals with the column ends. These ultra-strong connections will not unexpectedly disconnect under temperature changes, vibrations, or other stresses normally encountered in GC analyses. The open design allows visual confirmation of the seal between the column and the Press-Tight® union to ensure confidence in the connection. Hang the connector from the column cage to minimize stress on the connections.

Who will benefit from using Vu2 Union® connectors?

Any analyst using guard columns, transfer lines, or restrictor tubing; performing a dual-column analysis with columns connected in series; or seeking to repair a broken column will find Vu2 Union® connectors the simple, reliable, easy-to-use solution to their connection needs.

A guard column connected to an analytical column by a Vu2 Union® connector.



Kits include: Vu2 Union® body, 2 knurled nuts, 2 Press-Tight® unions, and 4 ferrules

Description	Ferrules Fit Column ID	qty.	cat. #
Vu2 Union Connector Kit	0.10–0.15 mm	kit	22220
Vu2 Union Connector Kit	0.18–0.28 mm	kit	21105
Vu2 Union Connector Kit	0.32 mm	kit	21106
Vu2 Union Connector Kit	0.45–0.53 mm	kit	21107
Knurled Nut		2-pk.	21108

Universal Press-Tight® Connectors

Description	5-pk.	25-pk.	100-pk.
Universal Press-Tight Connectors	20400	20401	20402
Universal Press-Tight Connectors, Deactivated	20429	20430	—
Universal Press-Tight Connectors, Siltek Deactivated	20480	20449	—

Graphite Ferrules for Vu2 Union® Connectors

- High-purity, high-density graphite.
- Stable to 450 °C.
- No binders that can off-gas or adsorb analytes.
- Smooth surface and clean edges.

Ferrule ID	Fits Column ID	Graphite 2-pk.	Graphite 10-pk.
0.3 mm	0.10–0.15 mm	22221	22222
0.4 mm	0.18–0.28 mm	20280	20281
0.5 mm	0.32 mm	20282	20283
0.8 mm	0.45–0.53 mm	20284	20285



SeCure® “Y” Connector Kits

- Connect two analytical columns to a transfer line or guard column.
- Use standard “Y” Press-Tight® connectors and 1/16" graphite ferrules.
- Reliable seal integrity—will not unexpectedly disconnect during temperature-programmed analyses.
- Open design allows visual confirmation of the seal for added confidence in the connection.
- Fit both Restek cage designs.

Combine the simplicity of a “Y” Press-Tight® connector with the strength of a metal union. The ferrules and knurled nuts hold the fused silica tubing in place, which prevents the tubing from unexpectedly disconnecting, even at temperatures as high as 400 °C.

The SeCure® “Y” connector’s open design allows visual confirmation of the seal.

Dual-column confirmational analysis with a single injection—one of the SeCure® “Y” connector’s many uses.



Fit both Restek cage designs.



**Secure, reliable
column-to-column
connections!**

Kits include: SeCure® “Y” connector body, 3 knurled nuts, “Y” Universal Press-Tight® union, 3 ferrules.


Description	Ferrules Fit Column ID	qty.	cat.#
SeCure “Y” Connector Kit	0.18/0.25/0.28 mm	kit	20276
SeCure “Y” Connector Kit	0.32 mm	kit	20277
SeCure “Y” Connector Kit	0.45/0.53 mm	kit	20278
Knurled Nut		3-pk.	20279

Universal “Y” Press-Tight® Connectors

An alternative method of performing dual-column confirmational analyses!

- Split sample flow onto two columns—perform confirmation analysis with a single injection.
- Split a single column flow to two detectors.

Description	ea.	3-pk.
Universal “Y” Press-Tight Connector	20405	20406
Universal “Y” Press-Tight Connector, Deactivated	20405-261	20406-261
Universal “Y” Press-Tight Connector, Siltek Deactivated	20485	20486



Graphite Ferrules for SeCure® “Y” Connectors


- Preconditioned to minimize out-gassing.
- High-purity, high-density graphite.
- Stable to 450 °C.
- No binders that can off-gas or adsorb analytes.
- Smooth surface and clean edges.

Ferrule ID	Fits Column ID	Graphite 10-pk.	Graphite 50-pk.
0.4 mm	0.10/0.15/0.18/0.25/0.28 mm	20200	20227
0.5 mm	0.32 mm	20201	20228
0.8 mm	0.45/0.53 mm	20202	20224



Press-Tight® Connectors


- Deactivated Press-Tight® connectors maintain complete inertness for the GC flow path.
- Siltek®-deactivated connectors are ideal for organochlorine pesticides analysis.
- Fit 0.33–0.74 mm OD columns (Restek 0.1–0.53 mm ID).



Universal Press-Tight® Connectors

- Connect a guard column to an analytical column.
- Repair a broken column.
- Connect a column outlet to a transfer line.

Description	5-pk.	25-pk.	100-pk.
Universal Press-Tight Connectors	20400	20401	20402
Universal Press-Tight Connectors, Deactivated	20429	20430	—
Universal Press-Tight Connectors, Siltek Deactivated	20480	20449	—




Universal “Y” Press-Tight® Connectors

An alternative method of performing dual-column confirmational analyses!

- Split sample flow onto two columns—perform confirmation analysis with a single injection.
- Split a single column flow to two detectors.

Description	ea.	3-pk.
Universal “Y” Press-Tight Connector	20405	20406
Universal “Y” Press-Tight Connector, Deactivated	20405-261	20406-261
Universal “Y” Press-Tight Connector, Siltek Deactivated	20485	20486



Universal Angled “Y” Press-Tight® Connectors

- Perform confirmation analysis with a single injection.
- Inlet and outlet ends conform to the column curvature—alleviates column-end connection strain.

Description	ea.	3-pk.
Universal Angled “Y” Press-Tight Connector	20403	20404
Universal Angled “Y” Press-Tight Connector, Deactivated	20403-261	20404-261
Universal Angled “Y” Press-Tight Connector, Siltek Deactivated	20487	20469



Polyimide Resin

Securely connects a Press-Tight® connector to a fused silica column.

Description	Max. Temp.	qty.	cat.#
Polyimide Resin	350 °C	5 grams	20445

MXT®-Union Connector Kits for Fused Silica Columns

- Low-dead-volume, leak-tight connection.
- Reusable.
- Siltek® treatment ensures maximum inertness.
- Ideal for connecting a guard column or transfer line to an analytical column.
- Use to oven temperatures of 360 °C.
- Available in union and “Y” configurations.
- Can also be used for connecting fused silica to metal.

These MXT® connectors can be used with fused silica tubing because of a Valcon polyimide, 1/32-inch, one-piece fused silica adaptor. This unique graphite-reinforced composite allows a capillary column to slide into the adaptor and be locked in place simply by loosening and tightening the fitting.



MXT®-Union Connector Kits for Fused Silica Columns

Each kit contains the MXT® union, two 1/32-inch nuts, and two one-piece fused silica adaptors.

Description	qty.	cat.#
For 0.25 mm ID Fused Silica Columns	kit	21386
For 0.32 mm ID Fused Silica Columns	kit	21385
For 0.53 mm ID Fused Silica Columns	kit	21384

MXT® “Y”-Union Connector Kits for Fused Silica Columns

Each kit contains the MXT® union, three 1/32-inch nuts, and three one-piece fused silica adaptors.



Description	qty.	cat.#
For 0.25 mm ID Fused Silica Columns	kit	21389
For 0.32 mm ID Fused Silica Columns	kit	21388
For 0.53 mm ID Fused Silica Columns	kit	21387

1/32-Inch Replacement Nut

Description	qty.	cat.#
1/32" Replacement Nut	5-pk.	20389



Valco® Connectors—One-Piece Valcon Polyimide Adaptor Ferrule for Fused Silica

Fused silica adaptor ferrules are made from Valcon polyimide, a unique graphite-reinforced composite specially prepared to maximize mechanical stability at temperatures up to 350 °C. The determining factor for selecting adaptor ferrule size is the fused silica tubing OD.

1/32-Inch Valco® Adaptor Ferrules (Valcon Polyimide)

Tubing OD	Tubing ID	Valco #	qty.	cat.#
0.25 ≤ 0.40 mm	0.25 mm	FS.4-5	5-pk.	20137
0.40 ≤ 0.50 mm	0.32 mm	FS.5-5	5-pk.	20140
0.50 ≤ 0.80 mm	0.53 mm	ZF.5V-5	5-pk.	20141
1/32" Replacement Nut			5-pk.	20389



Ferrule Removal Kit

The tapered tools in this kit have teeth designed to grip and remove fused silica adaptor ferrules that have become stuck in the fitting detail. Each kit has two tools: one for removing 1/32-inch adaptor ferrules and one for removing 1/16-inch adaptor ferrules.

Description	Valco #	qty.	cat.#
Ferrule Removal Kit	FRK1	kit	20146



22358

**Universal plug set for
battery charger included
in all kits.**



Electronic Rechargeable Crimpers and Decappers

- Easy to use; comfortable grip.
- Hundreds of operations from one charge.
- Adjustable crimping force.
- Large battery allows for faster charge cycle.
- All kits include a universal plug set for the battery charger.
- For 11 mm and 20 mm caps.
- One-year warranty.

These electronic crimpers and decappers have a rechargeable 6.4-volt battery installed. The large battery allows for quick, powerful operation and a faster charge cycle, minimizing downtime. Charging the battery takes thirty minutes to two hours. The universal plug set includes U.S., European, UK, and Australian plug clips.

Description	Size	qty.	cat.#
Electronic Crimper	11 mm	kit	22358
Electronic Crimper	20 mm	kit	22359
Electronic Decapper	11 mm	kit	22360
Electronic Decapper	20 mm	kit	22361
Replacement Battery for Electronic Crimpers and Decappers		ea.	22362



Crimper

Decapper

**Safer than removing
caps with pliers, knives,
or screwdriver blades!**

Easy Grip Manual Crimpers and Decappers

Our new Easy Grip crimpers and decappers feature tough, light, glass-filled plastic bodies with curved handles that improve hand comfort during use. The bottom-pull handle allows for a steadier hold than top-push handles. An easily viewed adjustment knob is located at the head of the product. The clearly shown + and – symbols, along with directional arrows, simplify adjusting the intensity of the crimp/decap needed. The knob is also designed to indicate when the crimp setting has been reached, when it fully contacts the body of the product.

Description	Size	qty.	cat.#
Crimper	11 mm	ea.	23396
Crimper	20 mm	ea.	23398
Decapper	11 mm	ea.	23397
Decapper	20 mm	ea.	23399

2.0 mL Crimp-Top Vials, 12 x 32 mm, 11 mm

Choose with or without white graduated marking spots.

Description	Color	Material	100-pk.	1,000-pk.
Vial w/White Graduated Marking Spot	Clear	Glass	24383	24384
Vial w/White Graduated Marking Spot	Amber	Glass	24385	24386
Vial without Graduated Marking Spot	Clear	Glass	21152	21153



24385

24383

2.0 mL, 11 mm Aluminum Crimp Seals With Septa

Seal Color	Septa Material	100-pk.	500-pk.	1,000-pk.
Silver	PTFE/Natural Rubber	21174	—	21175
Blue	PTFE/Red Rubber	24351	—	24352
Green	PTFE/Red Rubber	24353	—	24354
Red	PTFE/Red Rubber	24355	—	24356
Yellow	PTFE/Red Rubber	24357	—	24358
Mixed	PTFE/Rubber	—	21724	—
Silver	PTFE/Silicone	24359	—	24360
Blue	PTFE/Silicone	24361	—	24362
Green	PTFE/Silicone	24363	—	24364
Red	PTFE/Silicone	24365	—	24366
Yellow	PTFE/Silicone	24367	—	24368
Mixed	PTFE/Silicone	—	21725	—
Silver	PTFE/Silicone/PTFE	24369	—	24370



21724

2.0 mL, 11 mm crimp-top vials are compatible with PerkinElmer Autosystem GC, AI-1, Integral 4000, ISS 100, ISS 200, LC 600 42 vial tray, 420/B, and 4900 instruments.

2.0 mL Crimp Vial Convenience Kits (Vials, Caps & Septa)

Vials packaged in a clear-lid tray. Caps with septa packaged in a plastic bag.

Description	100-pk.	1,000-pk.
Clear 2.0 mL Vial, Deactivated, Silver Seal, PTFE/Natural Rubber Septa	24671	24672
Amber 2.0 mL Vial, Deactivated, Silver Seal, PTFE/Natural Rubber Septa	24673	24674
Clear 2.0 mL Vial, Untreated, Silver Seal, PTFE/Natural Rubber Septa	21196	21197
Amber 2.0 mL Vial, Untreated, Silver Seal, PTFE/Natural Rubber Septa	21198	21199
Clear 2.0 mL Vial, Untreated, Silver Seal, PTFE/Silicone Septa	24646	24647
Amber 2.0 mL Vial, Untreated, Silver Seal, PTFE/Silicone Septa	24648	24649



24671

Inserts for 2.0 mL, 11 mm Crimp-Top & 2.0 mL, 9 mm Short-Cap, Screw-Thread Vials

Description	Volume	Material	100-pk.	1,000-pk.
Big Mouth Insert w/Bottom Spring	50 µL	Glass	24513	21782
Big Mouth Insert w/Bottom Spring	250 µL	Glass	21776	21777
Big Mouth Insert w/Glass Flange (Step Design)*	250 µL	Glass	24516	21779
Insert, Flat Bottom	350 µL	Glass	21780	24517
Insert, Flat Bottom w/ID Ring	350 µL	Glass	24692	24693
Big Mouth Insert w/Bottom Spring	250 µL	Polypropylene	24518	—
Big Mouth Insert w/Bottom Spring & Graduated Markings	250 µL	Polypropylene	24518A	—
Big Mouth Insert, Top Flange	250 µL	Polypropylene	24519	—
Big Mouth Insert, No Spring	250 µL	Polypropylene	24520	—

*Big Mouth insert w/glass flange (step design) not to be used with 9 mm screw-thread vials.



21776



24692



24518A

2.0 mL Crimp-Top Vial With 100 µL Insert

- Plastic vial.
- Choice of glass or polypropylene insert.

Description	100-pk.	1,000-pk.
Clear Plastic Vial w/100 µL Polypropylene Insert	24651	24652
Clear Plastic Vial w/100 µL Glass Insert	24653	—



24651



2.0 mL, 11 mm Poly Crimp Seal Caps: Snap-On or Crimp

- Works on any crimp-style vial.

The Poly Crimp Seal is versatile, working as either a snap-on or crimp-top cap. Simply use a standard crimping tool to secure the Poly Crimp Seal onto any crimp-top vial. It's that easy!



Seal Color	Liner Material	100-pk.	400-pk.	1,000-pk.
Clear	PTFE/Butyl Rubber	24433	—	24434
Clear	PTFE/Silicone	24443	—	24444
Blue	PTFE/Silicone	24445	—	24446
Clear	PTFE/Silicone/PTFE	24453	—	24454
Blue	PTFE/Silicone/PTFE	24455	—	24456
Mixed	PTFE/Silicone/PTFE	—	21728	—



21731

2.0 mL, 11 mm GC Snap Ring Cap With Septum

- Snaps on any crimp-style vial.
- Save money! Use this snap cap when you don't need to crimp.

Description	Liner/Septa Material	100-pk.	1,000-pk.
Polypropylene Snap Ring Cap w/Liner	PTFE, 10 mil	21729	21730
Polypropylene Snap Ring Cap w/Septum	PTFE/Butyl Rubber	21731	21732
Polypropylene Snap Ring Cap w/Septum	PTFE/Silicone	21733	21734



22788

Certified Autosampler Vial Kits

Certified Vials, 2.0 mL Screw-Thread Vials

- Certificates enclosed with each kit.
- Vials of clear or amber borosilicate glass with ID marking spots.
- Closures with pre-inserted septa.
- Each kit sealed for integrity.

Certification Parameters Include:

Vial Dimensions:	Height, diameter, bottom thickness, neck length, thread profile, and annealing
Cap/Septum:	Diameter, height, thread integrity, center flash, septa insertion, sealing/resealing test, residue by headspace GC, and extractables
Chemical Test:	LC Test: nonvolatile residue
	GC Test: volatile residue



22792

Description	100-pk.
Assembled Clear 2.0 mL Vial w/Marking Spot, Cap, Bonded PTFE/Silicone Slit Septa	22789
Assembled Amber 2.0 mL Vial w/Marking Spot, Cap, Bonded PTFE/Silicone Slit Septa	22788
Unassembled Clear 2.0 mL Vial w/Marking Spot, Cap, Bonded PTFE/Silicone Septa	22792
Unassembled Amber 2.0 mL Vial w/Marking Spot, Cap, Bonded PTFE/Silicone Septa	22790
Unassembled Clear 2.0 mL High-Recovery Vial w/Marking Spot, Cap, Bonded PTFE/Silicone Slit Septa	22793
Unassembled Amber 2.0 mL Vial w/Marking Spot, Cap, Bonded PTFE/Silicone Slit Septa	22791

2.0 mL, 9 mm Short-Cap, Screw-Thread Vials, 12 x 32 mm

- Fit all 2.0 mL, 12 x 32 mm, crimp-top vial-based autosamplers.

2.0 mL, 9 mm Short-Cap, Screw-Thread Vials (vial only)

Description	Color	100-pk.	1,000-pk.
Short-Cap Vial w/White Graduated Marking Spot	Clear	21140	21141
Short-Cap Vial w/White Graduated Marking Spot	Amber	21142	21143
Short-Cap Vial without Graduated Marking Spot	Clear	21154	21155



21140

2.0 mL, 9 mm Short-Cap, Screw-Vial Closures (Polypropylene, preassembled)

Cap Color	Liner Material	100-pk.	500-pk.	1,000-pk.
Blue	PTFE/Red Rubber	24473	—	24474
Mixed	PTFE/Red Rubber	—	24668	—
Blue	PTFE/Silicone	24485	—	24486
Green	PTFE/Silicone	24487	—	24488
Yellow	PTFE/Silicone	24493	—	24494
Mixed	PTFE/Silicone	—	24669	—
Blue	PTFE/Silicone/PTFE	24497	—	24498
Black	PTFE/Silicone/PTFE	24495	—	24496
Natural	PTFE/Silicone/PTFE	24501	—	24502
Red	PTFE/Silicone/PTFE	24503	—	24504
Yellow	PTFE/Silicone/PTFE	24505	—	24506
Mixed	PTFE/Silicone/PTFE	—	24670	—



24668

2.0 mL, 9 mm short-cap, screw-thread vials are compatible with PerkinElmer AI-1, ISS 100, ISS 200, and LC 600 42 vial tray instruments.

2.0 mL Sample Vial Racks

- Racks feature alphanumeric indexing for easier vial identification.
- Racks can be stacked for efficient storage.
- Fits most 2.0 mL, 12 x 32 mm vials (vials sold separately).

Description	Capacity	qty.	cat.#	qty.	cat.#
Polypropylene Storage Rack for 12 x 32 mm Vials	50 vials, 5 x 10	ea.	22856	5-pk.	22857



22856



All vials undeactivated unless otherwise noted.

2.0 mL, 8 mm screw-thread vials are compatible with PerkinElmer Autosystem GC, 420/B, and 4900 instruments.

2.0 mL Screw-Thread Vials, 12 x 32 mm, 8 mm/425 Thread

- Fit all 2.0 mL, 12 x 32 mm, screw-thread 8 mm/425 vial-based autosamplers.

2.0 mL, 8 mm Screw-Thread Vials (vial only)

Description	Volume	Color	100-pk.	1,000-pk.
Vial w/White Graduated Marking Spot	2.0 mL	Clear	24619	24620
Vial w/White Graduated Marking Spot	2.0 mL	Amber	24621	24622

2.0 mL, 8 mm Caps and Septa (preassembled)

Cap Color	Septa Material	100-pk.	1,000-pk.
Black	Red PTFE/Silicone, 0.065"	21149	21720
Black Top Hat	PTFE/Silicone	21721	21722

Caps and Septa for 2.0 mL, 8 mm Screw-Thread Vials

Description	Septa Material	100-pk.	1,000-pk.
Black Polypropylene, Open-Hole Caps		21176	21177
Septa, 8 mm x 0.045"	Red PTFE/Silicone	21178	21179
Septa, 8 mm x 0.065"	Red PTFE/White Silicone	21795	21147

2.0 mL Autosampler Vial Convenience Kits

- Vials packaged in a clear-lid tray. Preassembled caps with septa packaged separately in a plastic bag.
- Black polypropylene open-hole caps and 8 mm red PTFE/silicone septa, 0.065".

Description	100-pk.	1,000-pk.
Clear 2.0 mL Vial, Silcote CL7-Deactivated, Black Cap, Red PTFE/Silicone Septa, 0.065"	24638	24639
Amber 2.0 mL Vial, Silcote CL7-Deactivated, Black Cap, Red PTFE/Silicone Septa, 0.065"	24640	24641
Clear 2.0 mL Vial, Untreated, Black Cap, Red PTFE/Silicone Septa, 0.065"	21192	21193
Amber 2.0 mL Vial, Untreated, Black Cap, Red PTFE/Silicone Septa, 0.065"	21194	21195

2.0 mL Preassembled Vial Kits

8 mm/425 Screw-Thread, Unmarked Vials, Septa, and Caps

Caps attached to vials.

Description	100-pk.	1,000-pk.
Clear 2.0 mL Vial, Black Cap, Red PTFE/Silicone Septa, 0.045"	24630	24631
Amber 2.0 mL Vial, Black Cap, Red PTFE/Silicone Septa, 0.045"	24632	24633

Headspace Screw-Thread Vials (18 mm)

Description	Volume	Color	Dimensions	100-pk.	1,000-pk.
Headspace Vial	10 mL	Clear	22 x 45 mm	23084	23085
Headspace Vial	10 mL	Amber	22 x 45 mm	23088	23089
Headspace Vial	20 mL	Clear	22 x 75 mm	23082	23083
Headspace Vial	20 mL	Amber	22 x 75 mm	23086	23087

Caps not included.

**Magnetic Screw-Thread Caps (18 mm)**

Description	Septa Material	100-pk.	1,000-pk.
Magnetic Caps and Septa	PTFE/Silicone	23090	23091
Magnetic Caps and Septa	PTFE/Silicone for SPME	23092	23093
Magnetic Caps and Septa	PTFE/Red Chlorobutyl	23094	23095

**Headspace Crimp Vials (20 mm)**

Description	Volume	Color	Dimensions	100-pk.	1,000-pk.
Headspace Vial	6 mL	Clear	22 x 38 mm	21166	21167
Headspace Vial, Flat Bottom	10 mL	Clear	23 x 46 mm	24683	24684
Headspace Vial, Rounded Bottom	10 mL	Clear	23 x 46 mm	21164	21165
Headspace Vial, Flat Bottom	20 mL	Clear	23 x 75 mm	24685	24686
Headspace Vial, Rounded Bottom	20 mL	Clear	23 x 75 mm	21162	21163
Headspace Vial	27 mL	Clear	30 x 60 mm	21160	21161

Vial-to-instrument compatibility are designated in instrument reference chart.


**Aluminum Seals w/Septa (20 mm, preassembled)**

Description	Cap Color	Septa Material	100-pk.	1,000-pk.
Seals w/Septa	Silver	PTFE/Gray Butyl Rubber	21761	21762
Seals w/Septa	Silver	PTFE/Silicone	21763	21764
Pressure Release Seals w/Septa	Silver	PTFE/Gray Butyl Rubber	21765	21766
Pressure Release Seals w/Septa	Silver	PTFE/Silicone	21767	21768

**Magnetic Seals w/Septa (20 mm, preassembled)**

Description	Cap Color	Septa Material	100-pk.	1,000-pk.
Magnetic Seals w/Septa, with 5 mm Hole	Gold	PTFE/Silicone	22833	22834
Magnetic Seals w/Septa, with 8 mm Hole	Gold	PTFE/Silicone	22831	22832
Magnetic Seals w/Septa, with 8 mm Hole	Gold	PTFE/Butyl	22835	22836
BiMetal Magnetic Seals w/Septa, with 8 mm Hole	Red/Silver	PTFE/Silicone	22441	22442
BiMetal Magnetic Seals w/Septa, with 8 mm Hole	Blue/Silver	PTFE/Silicone	22443	22444


5 mm hole is compatible with the following systems: Carlo Erba HS500/HS800, CTC 500, Fisons HS500/HS800 and Varian/Chrompack 9020/25. 8 mm hole is compatible with the Combi Pal.





24952

24812



24818

Autosampler Syringes for PerkinElmer Autosystem and Clarus 500 GCs

- Hamilton and SGE syringes are designed and tested to meet critical autosampler performance needs.
- Needle point styles are designed to withstand multiple, rapid injections through a septum.

Hamilton

Volume	Needle Term.	Needle Gauge	Needle Length	Point Style	Hamilton Model	cat.#	qty.	Restek cat.#
5 μ L	ASN	23	2.756"	3	75ASN/PE	88035	ea.	24953
5 μ L	ASN	26	2.756"	3	75ASN/PE	88040	ea.	24952

SGE

Volume	Needle Term.	Needle Gauge	Needle Length	Point Style	SGE Model	cat.#	qty.	Restek cat.#
0.5 μ L	R	23	70 mm	Cone	0.5BR-PE-0.63	000478	ea.	24811
0.5 μ L	R	26	70 mm	Cone	0.5BR-PE-0.47	000475	ea.	24810
5 μ L	F	23	70 mm	Cone	5F-PE-0.63	001954	ea.	24813
5 μ L*	F	23	70 mm	Cone	5F-PE-GT-0.63	001957	ea.	24815
5 μ L	F	26	70 mm	Cone	5F-PE-0.47	001953	ea.	24812
5 μ L*	F	26	70 mm	Cone	5F-PE-GT-0.47	001955	ea.	24814
50 μ L	F	23	70 mm	Cone	50F-PE-0.63	004670	ea.	24816

*Gas-tight.

Replacement Needle and Plunger Kit for PerkinElmer Autosampler Syringes

SGE

Syringe Volume	Needle Gauge	Needle Length	Point Style	SGE cat.#	qty.	Restek cat.#
0.5 μ L	23	70 mm	Cone	033765	kit	24818
0.5 μ L	26	70 mm	Cone	033750	kit	24817

Guide to Needle Termination Codes

Hamilton:

(ASN) Autosampler Cemented Needle

SGE:

(F) Fixed Needle

(R) Removable Needle

Restek Super-Clean Gas Filters

- High-purity output ensures 99.9999% pure gas (at max. flow of 2 L/min).
- “Quick connect” fittings for easy, leak-tight cartridge changes.
- Glass inside to prevent diffusion; polycarbonate housing outside for safety.
- All traps measure 10 ⁵/₈" x 1 ³/₄" (27 x 4.4 cm).
- Each base plate unit measures 4" x 4" x 1 ⁷/₈" (10.2 x 10.2 x 4.8 cm).

Table I: Each Super-Clean gas filter provides high-purity outlet gas.

Type of Filter	Outlet Gas Quality (%)	Maximum Pressure/ Maximum Flow Rates	Use for:	Indicator Color Change	Capacity			Estimated Lifetime (years)
					H ₂ O (g)	O ₂ (mL)	Hydrocarbons (g)	
Moisture cat.# 22028	>99.9999	11 bar 159 psi/ 7 L/min	Inert carrier gas Air Hydrogen	Yellow/orange to clear	7.2	—	—	>2
Oxygen cat.# 22029	>99.9999	11 bar 159 psi/ 7 L/min	Inert carrier gas	Green to grey	NA	1,000	—	>2
Hydrocarbons cat.# 22030	>99.9999	11 bar 159 psi/ 7 L/min	Inert carrier gas Air Hydrogen	No indicator	NA	—	12 ³	>2
Fuel Gas ¹ cat.# 22022	>99.9999	11 bar 159 psi/ 7 L/min	Inert carrier gas Air Hydrogen	Yellow/orange to clear	3.5	—	24 ³	>1.5
Triple ² cat.# 22020	>99.9999	11 bar 159 psi/ 7 L/min	Inert carrier gas	Yellow/orange to clear Green to grey	1.8	500	4 ³	>1
Helium Specific ² cat.# 21982	>99.9999	11 bar 159 psi/ 7 L/min	Helium	Yellow/orange to clear Green to grey	1.8	500	—	>1

¹Removes hydrocarbons and moisture.

²Removes hydrocarbons, moisture, and oxygen.

³As *n*-butane.



did you
know?

All Restek Super-Clean gas filter cartridges (except hydrocarbon filter cat.# 22030) feature easy-to-read indicators. The indicator code is shown on every trap, so there is no confusion about when to replace it.



22020



21982



base plate

Restek Super-Clean Gas Filter Kits and Replacements

Description	qty.	cat.#
Carrier Gas Cleaning Kit Includes: mounting base plate, 1/8" inlet/outlet fittings, and oxygen/moisture/hydrocarbon triple gas filter	kit	22019
Fuel Gas Purification Kit Includes: mounting base plate, 1/8" inlet/outlet fittings, and hydrocarbon/moisture fuel gas filter	kit	22021
Ultra-High Capacity Hydrocarbon Filter	ea.	22030
Ultra-High Capacity Moisture Filter	ea.	22028
Ultra-High Capacity Oxygen Filter	ea.	22029
Replacement Triple Gas Filter (removes oxygen, moisture, and hydrocarbons)	ea.	22020
Replacement Fuel Gas Filter (removes moisture and hydrocarbons)	ea.	22022
Helium-Specific Carrier Gas Cleaning Kit Includes: mounting base plate, 1/8" inlet/outlet fittings, and oxygen/moisture/hydrocarbon helium-specific filter	kit	21983
Replacement Helium-Specific Gas Filter (removes oxygen, moisture, and hydrocarbons)	ea.	21982
Gas Filter Bundle Kit Includes: one triple gas filter (cat.# 22020) and two fuel gas filters (cat.# 22022)	kit	22031



Oxygen and Moisture Traps

Restek highly recommends oxygen and moisture traps for make-up gas when operating sensitive detectors such as electron capture detectors (ECD). The hydrogen reaction gas for sensitive electrolytic conductivity detectors (ELCD) also requires a hydrocarbon trap to remove trace impurities.

Overview of Restek Ultra-High Purity (UHP) Gas Regulators

- Regulators feature metal-to-metal seals throughout for long-term leak-tightness.
- Metal diaphragm outlet valve ensures gas purity.
- Each regulator is helium leak-test-certifiable to 1×10^{-8} scc/sec.
- Temperature range: -40 °C to 60 °C.

Ultra-High Purity (UHP) Brass Body Gas Regulators

UHP brass regulators are the best choice when using ultra-high purity carrier gas for sensitive GC applications using MS, PID, or ECD detection methods. They feature reduced internal dead-volume relative to stainless steel bodies. The metal valve diaphragm ensures leak-free shutoff. Oxidation-resistant chrome plating maintains a like-new appearance.

Dual-Stage Ultra-High Purity Chrome-Plated Brass Gas Regulators

- Oxidation-resistant, chrome-plated.
- Most stable outlet pressure control.
- Secondary pressure regulation not needed.
- Most widely used regulator.
- Less internal volume than stainless steel gas regulators.



Inlet gauge: 0 to 4,000 psig (0–27,579 kPa)
Outlet assembly: diaphragm valve, 1/4" tube fitting

Fitting	Outlet Pressure	Outlet Gauge	qty.	cat.#
CGA 580 (N ₂ , He, Ar)	0 to 100 psig (0–689 kPa)	30" – 0 to 200 psig (0–1,379 kPa)	ea.	21667
CGA 350 (H ₂ , P ₂)	0 to 100 psig (0–689 kPa)	30" – 0 to 200 psig (0–1,379 kPa)	ea.	21668
CGA 590 (Air)	0 to 100 psig (0–689 kPa)	30" – 0 to 200 psig (0–1,379 kPa)	ea.	21669
DIN 477 #1 (H ₂)	0 to 7 bar (0–100 psig)	30" – 0 to 14 bar (0–200 psig)	ea.	22369
DIN 477 #6 (He, Ar)	0 to 7 bar (0–100 psig)	30" – 0 to 14 bar (0–200 psig)	ea.	22368
DIN 477 #9 (Air)	0 to 7 bar (0–100 psig)	30" – 0 to 14 bar (0–200 psig)	ea.	22370
DIN 477 #10 (N ₂)	0 to 7 bar (0–100 psig)	30" – 0 to 14 bar (0–200 psig)	ea.	22371

NOTE: CGA fittings are for U.S. use; DIN fittings are for European use.

Single-Stage Ultra-High Purity Chrome-Plated Brass Gas Regulators

- Oxidation-resistant, chrome-plated.
- Use when there is secondary pressure regulation downstream.
- Identical gas purity protection as with dual-stage gas regulators.


Inlet gauge: 0 to 4,000 psig (0–27,579 kPa)
Outlet assembly: diaphragm valve, 1/4" tube fitting

Fitting	Outlet Pressure	Outlet Gauge	qty.	cat.#
CGA 580 (N ₂ , He, Ar)	0 to 100 psig (0–689 kPa)	30" – 0 to 200 psig (0–1,379 kPa)	ea.	20646
CGA 350 (H ₂ , P ₂)	0 to 100 psig (0–689 kPa)	30" – 0 to 200 psig (0–1,379 kPa)	ea.	20647
CGA 590 (Air)	0 to 100 psig (0–689 kPa)	30" – 0 to 200 psig (0–1,379 kPa)	ea.	20648
DIN 477 #1 (H ₂)	0 to 7 bar (0–100 psig)	30" – 0 to 14 bar (0–200 psig)	ea.	22373
DIN 477 #6 (He, Ar)	0 to 7 bar (0–100 psig)	30" – 0 to 14 bar (0–200 psig)	ea.	22372
DIN 477 #9 (Air)	0 to 7 bar (0–100 psig)	30" – 0 to 14 bar (0–200 psig)	ea.	22374
DIN 477 #10 (N ₂)	0 to 7 bar (0–100 psig)	30" – 0 to 14 bar (0–200 psig)	ea.	22375

NOTE: CGA fittings are for U.S. use; DIN fittings are for European use.

Ultra-High Purity Chrome-Plated Brass Line Gas Regulator

- Oxidation-resistant, chrome-plated.
- Use where you need to reduce the line pressure by 20 psig (138 kPa) or more.
- Same purity protection as high-pressure cylinder regulators.



Inlet connections: 1/4" FPT
Outlet assembly: 1/4" FPT port

Fitting	Outlet Pressure	Outlet Gauge	qty.	cat.#
1/4" female NPT ports*	0–50 psig (0–345 kPa)	30" – 0 to 100 psig (0–689 kPa)	ea.	21666
1/4" female NPT ports*	0–100 psig (0–689 kPa)	30" – 0 to 200 psig (0–1,379 kPa)	ea.	22452

*Order appropriate male connector, pipe-to-tube fittings.

Swagelok® Male Connector, Pipe-to-Tube Fittings

Fitting Type	Size (inches)	Similar to Swagelok	Brass		Stainless Steel	
			qty.	cat.#	qty.	cat.#
Male Connector	1/4" to 1/2" NPT	400-1-4	10-pk.	23134	2-pk.	23184
Male Connector	1/8" to 1/4" NPT	200-1-4	10-pk.	23136	2-pk.	23186
Tube End Reducer	1/4" to 1/8"	200-R-4	5-pk.	23129	2-pk.	23179



23134

23179

Ultra-High Purity (UHP) Stainless Steel Body Gas Regulators

UHP stainless steel regulators are the standard for ultra-high-purity and corrosion-resistant pressure regulation. They are more easily purged of atmospheric components compared to brass gas regulators, making them ideal for the most demanding applications. Stainless steel is especially useful in atmospheres of dry corrosive gases such as hydrogen.

Dual-Stage Ultra-High Purity Stainless Steel Gas Regulators

- Most stable outlet pressure control.
- Secondary pressure regulation not needed.

Fitting	Outlet Pressure	Outlet Gauge	qty.	cat.#
CGA 580 (N ₂ , He, Ar)	0 to 100 psig (0–689 kPa)	30" – 0 to 200 psig (0–1,379 kPa)	ea.	20662
CGA 350 (H ₂ , P ₂)	0 to 100 psig (0–689 kPa)	30" – 0 to 200 psig (0–1,379 kPa)	ea.	20663
CGA 590 (Air)	0 to 100 psig (0–689 kPa)	30" – 0 to 200 psig (0–1,379 kPa)	ea.	20664
DIN 477 #1 (H ₂)	0 to 7 bar (0–100 psig)	30" – 0 to 14 bar (0–200 psig)	ea.	22377
DIN 477 #6 (He, Ar)	0 to 7 bar (0–100 psig)	30" – 0 to 14 bar (0–200 psig)	ea.	22376
DIN 477 #9 (Air)	0 to 7 bar (0–100 psig)	30" – 0 to 14 bar (0–200 psig)	ea.	22378
DIN 477 #10 (N ₂)	0 to 7 bar (0–100 psig)	30" – 0 to 14 bar (0–200 psig)	ea.	22379

NOTE: CGA fittings are for U.S. use; DIN fittings are for European use.

Single-Stage Ultra-High Purity Stainless Steel Gas Regulators

- Use when there is secondary pressure regulation downstream.
- Identical gas purity protection as with dual-stage gas regulators.

Fitting	Outlet Pressure	Outlet Gauge	qty.	cat.#
CGA 580 (N ₂ , He, Ar)	0 to 100 psig (0–689 kPa)	30" – 0 to 200 psig (0–1,379 kPa)	ea.	20665
CGA 350 (H ₂ , P ₂)	0 to 100 psig (0–689 kPa)	30" – 0 to 200 psig (0–1,379 kPa)	ea.	20666
CGA 590 (Air)	0 to 100 psig (0–689 kPa)	30" – 0 to 200 psig (0–1,379 kPa)	ea.	20667
DIN 477 #1 (H ₂)	0 to 7 bar (0–100 psig)	30" – 0 to 14 bar (0–200 psig)	ea.	22380
DIN 477 #6 (He, Ar)	0 to 7 bar (0–100 psig)	30" – 0 to 14 bar (0–200 psig)	ea.	22445
DIN 477 #9 (Air)	0 to 7 bar (0–100 psig)	30" – 0 to 14 bar (0–200 psig)	ea.	22446
DIN 477 #10 (N ₂)	0 to 7 bar (0–100 psig)	30" – 0 to 14 bar (0–200 psig)	ea.	22447

NOTE: CGA fittings are for U.S. use; DIN fittings are for European use.

Flexible Stainless Steel Hoses

Description	Length	Fittings	qty.	cat. #
Flexible Stainless Steel Hose	36"	1/4" Female NPT	ea.	21339
Flexible Stainless Steel Hose	18"	1/4" Female NPT	ea.	21340

Flammable Gas Flash Arrestor—Factory Mutual Approved*

- Gas flow shuts off in the event of a flashback.
- Flame extinguished—flame front prevented from reaching the gas supply.
- No gas flow restriction under normal operating conditions.

Description	Fittings	qty.	cat.#
Flammable Gas Flash Arrestor, Brass Body	1/4" NPTF	ea.	21334

*Approved for brass body servicing hydrogen, acetylene, propane, or natural gas only.

CGA Fittings

CGA-specified nuts and nipples with internal frit, 1/4-inch NPT nickel-plated brass.

Description	qty.	cat.#
CGA 580 Fitting (N ₂ , He, Ar)	ea.	21336
CGA 350 Fitting (H ₂ , P ₂)	ea.	21337
CGA 590 Fitting (Air)	ea.	21338



Inlet gauge: 0 to 4,000 psig (0–27,579 kPa)
Outlet assembly: diaphragm valve, 1/4" tube fitting

Inlet gauge: 0 to 4,000 psig (0–27,579 kPa)
Outlet assembly: diaphragm valve, 1/4" tube fitting



21334



21336

ordering note


International Fittings

All gas regulators are available with the following BS (British Standard) and DIN (German Industrial Standards Organization) connections. Please contact your local Restek representative for more information.

BS 341 #01	BS 341 #08	BS 341 #15	DIN 477 #06	DIN 477 #10	DIN 477 #14
BS 341 #02	BS 341 #10	DIN 477 #01	DIN 477 #07	DIN 477 #11	DIN 477 #15
BS 341 #03	BS 341 #13	DIN 477 #03	DIN 477 #08	DIN 477 #12	
BS 341 #04	BS 341 #14	DIN 477 #05	DIN 477 #09	DIN 477 #13	

Swagelok® Fittings (Brass & Stainless Steel)

Restek is pleased to offer one of the premier lines of fittings available for chromatographers in the market today. We can supply the entire line of Swagelok® fittings. If you don't see the exact product you're looking for, please call us or contact your Restek representative for a quote.




Fitting Type	Size	Swagelok #	Brass		316 Grade Stainless Steel	
			qty.	cat. #	qty.	cat. #
Nut	1/16"	102-1	20-pk.	23100	5-pk.	23150
	1/8"	202-1	40-pk.	23101	10-pk.	23151
	1/4"	402-1	40-pk.	23102	10-pk.	23152
Front Ferrule	1/16"	103-1	20-pk.	23103	10-pk.	23153
	1/8"	203-1	40-pk.	23104	20-pk.	23154
	1/4"	403-1	40-pk.	23105	20-pk.	23155
Back Ferrule	1/16"	104-1	20-pk.	23106	10-pk.	23156
	1/8"	204-1	40-pk.	23107	20-pk.	23157
	1/4"	404-1	40-pk.	23108	20-pk.	23158
Nut & Ferrule Set	1/16"	—	10-pk.	23109	2-pk.	23159
	1/8"	—	20-pk.	23110	5-pk.	23160
	1/4"	—	20-pk.	23111	5-pk.	23161
Plug	1/16"	100-P	5-pk.	23112	2-pk.	23162
	1/8"	200-P	10-pk.	23113	4-pk.	23163
	1/4"	400-P	10-pk.	23114	4-pk.	23164
Union	1/16"	100-6	3-pk.	23115	ea.	23165
	1/8"	200-6	5-pk.	23116	2-pk.	23166
	1/4"	400-6	5-pk.	23117	2-pk.	23167
Reducing Union	1/8" to 1/16"	200-6-1	5-pk.	23118	ea.	23168
	1/4" to 1/16"	400-6-1	5-pk.	23119	2-pk.	23169
	1/4" to 1/8"	400-6-2	5-pk.	23120	2-pk.	23170
Tee	1/16"	100-3	2-pk.	23121	ea.	23171
	1/8"	200-3	2-pk.	23122	ea.	23172
	1/4"	400-3	2-pk.	23123	ea.	23173
Cross	1/8"	200-4	2-pk.	23124	ea.	23174
	1/4"	400-4	2-pk.	23125	ea.	23175
Tube End Reducer	1/8" to 1/16"	100-R-2	5-pk.	23126	2-pk.	23176
	1/4" to 1/16"	100-R-4	5-pk.	23127	2-pk.	23177
	1/8" to 1/4"	400-R-2	5-pk.	23128	2-pk.	23178
	1/4" to 1/8"	200-R-4	5-pk.	23129	2-pk.	23179
Port Connector	1/8"	201-PC	5-pk.	23130	2-pk.	23180
	1/4"	401-PC	10-pk.	23131	2-pk.	23181
	1/8" to 1/4"	401-PC-2	5-pk.	23132	2-pk.	23182
Male Connector	1/8" to 1/8" NPT	200-1-2	10-pk.	23133	2-pk.	23183
	1/4" to 1/4" NPT	400-1-4	10-pk.	23134	2-pk.	23184
	1/16" to 1/8" NPT	100-1-2	5-pk.	23135	2-pk.	23185
	1/8" to 1/4" NPT	200-1-4	10-pk.	23136	2-pk.	23186
	1/4" to 1/8" NPT	400-1-2	10-pk.	23137	2-pk.	23187
Female Connector	1/8" to 1/8" NPT	200-7-2	5-pk.	23138	2-pk.	23188
	1/4" to 1/4" NPT	400-7-4	5-pk.	23139	2-pk.	23189
	1/4" to 1/8" NPT	400-7-2	5-pk.	23140	2-pk.	23190
Male & Female Quick Couplings	1/8" male*	QC4D-200	—	—	ea.	23191
	1/8" male	QC4S-200	—	—	ea.	23192
	1/8" female*	QC4B-200	—	—	ea.	23193
	1/4" male*	QC4D-400	—	—	ea.	23194
	1/4" male	QC4S-400	—	—	ea.	23195
	1/4" female*	QC4B-400	—	—	ea.	23196

*Includes self-sealing shutoff valve.

Swagelok® Fittings (Siltek®/Sulfinert® & Silcosteel®-CR Treated)

- Full line of treated 1/16", 1/8", and 1/4" fittings.
- Silcosteel®-CR treatment enhances corrosion resistance by 10x or more.
- For custom treatment on any Swagelok® fitting or other system parts not listed here, call us or contact your Restek representative.

Fitting Type	Size	Swagelok #	Siltek/Sulfinert Treated		Silcosteel-CR Treated	
			qty.	cat.#	qty.	cat.#
Union	1/16"	SS-100-6	ea.	22540	ea.	22575
	1/8"	SS-200-6	ea.	22541	ea.	22576
	1/4"	SS-400-6	ea.	22542	ea.	22577
	3/8"	SS-600-6	ea.	22909	ea.	22904
Tee	1/16"	SS-100-3	ea.	22543	ea.	22578
	1/8"	SS-200-3	ea.	22544	ea.	22579
	1/4"	SS-400-3	ea.	22545	ea.	22580
	3/8"	SS-600-3	ea.	22910	ea.	22905
Reducing Union	1/8" to 1/16"	SS-200-6-1	ea.	22546	ea.	22581
	1/4" to 1/16"	SS-400-6-1	ea.	22547	ea.	22582
	1/4" to 1/8"	SS-400-6-2	ea.	22548	ea.	22583
	3/8" to 1/4"	SS-600-6-4	ea.	22911	ea.	22906
Elbow	1/8"	SS-200-9	ea.	22549	ea.	22584
	1/4"	SS-400-9	ea.	22550	ea.	22585
Plug	1/8"	SS-200-P	ea.	22573	ea.	22620
	1/4"	SS-400-P	ea.	22574	ea.	22597
Cross	1/8"	SS-200-4	ea.	22551	ea.	22586
	1/4"	SS-400-4	ea.	22552	ea.	22587
Tube End Reducer	1/8" tube to 1/16"	SS-100-R-2	ea.	22553	ea.	22588
	1/4" tube to 1/16"	SS-100-R-4	ea.	22554	ea.	22589
	1/8" tube to 1/4"	SS-400-R-2	ea.	22555	ea.	22590
	1/4" tube to 1/8"	SS-200-R-4	ea.	22556	ea.	22591
Port Connector	1/8"	SS-201-PC	ea.	22557	ea.	22592
	1/4"	SS-401-PC	ea.	22558	ea.	22593
	1/8" tube to 1/4"	SS-401-PC-2	ea.	22559	ea.	22594
Male Connector	1/8" to 1/8" NPT	SS-200-1-2	ea.	22561	ea.	22595
	1/4" to 1/4" NPT	SS-400-1-4	ea.	22562	ea.	22596
	1/16" to 1/8" NPT	SS-100-1-2	ea.	22563	ea.	22610
	1/8" to 1/4" NPT	SS-200-1-4	ea.	22564	ea.	22611
	1/4" to 1/8" NPT	SS-400-1-2	ea.	22565	ea.	22612
	3/8" to 3/8" NPT	SS-600-1-6	ea.	22912	ea.	22907
Female Connector	1/8" to 1/8" NPT	SS-200-7-2	ea.	22566	ea.	22613
	1/4" to 1/4" NPT	SS-400-7-4	ea.	22567	ea.	22614
	1/4" to 1/8" NPT	SS-400-7-2	ea.	22568	ea.	22615
	1/8" to 1/4" NPT	SS-200-7-4	ea.	22569	ea.	22616
Bulkhead Union	1/8"	SS-200-61	ea.	22570	ea.	22617
	1/4"	SS-400-61	ea.	22571	ea.	22618

**Swagelok® Fitting Kits**

Save more than 40% by purchasing a Restek Swagelok® fittings kit compared to paying full price for the individual parts!

- Includes the most common assortment of 1/8" and 1/4" brass or stainless steel fittings.
- Parts list makes reordering easy.
- Parts come in sturdy toolbox for easy and convenient storage.



Description	qty.	cat.#
Swagelok Fitting Kit, Brass	kit	23141

Description	qty.	cat.#
Swagelok Fitting Kit, Stainless Steel	kit	23197



More Parts & Accessories for More GC Systems

Agilent
Bruker/Varian
PerkinElmer
Shimadzu
Thermo Scientific
and more!

www.restek.com/GCacc

Also look to Restek for:

GC Columns & Accessories | LC Columns & Accessories
Sample Preparation | Certified Reference Materials (CRMs) | Expert Support

PATENTS & TRADEMARKS

Restek patents and trademarks are the property of Restek Corporation. Other trademarks appearing in Restek literature or on its website are the property of their respective owners. The Restek registered trademarks used here are registered in the United States and may also be registered in other countries.



Lit. Cat.# GNM1159-UNV

© 2012 Restek Corporation. All rights reserved.
Printed in the U.S.A.

Restek U.S. • 110 Benner Circle • Bellefonte, PA 16823 • 1-814-353-1300 • 1-800-356-1688 • fax: 1-814-353-1309 • **www.restek.com**

Restek France • phone: +33 (0)1 60 78 32 10 • fax: +33 (0)1 60 78 70 90 • **www.restek.fr**

Restek GmbH • phone: +49 (0)6172 2797 0 • fax: +49 (0)6172 2797 77 • **www.restekgmbh.de**

Restek Ireland • phone: +44 (0)2890 814576 • fax: +44 (0)2890 814576 • e-mail: **restekireland@aol.com**

Restek Japan • phone: +81 (3)6459 0025 • fax: +81 (3)6459 0025 • e-mail: **restekjapan@restek.com**

Thames Restek U.K. LTD • phone: +44 (0)1494 563377 • fax: +44 (0)1494 564990 • **www.thamesrestek.co.uk**

